

Compare our taximeters range



AIR W

[Learn more](#)



POWER HD

[Learn more](#)



AIR S

[Learn more](#)



POWER UP

[Learn more](#)



PRIMUS
RS-01

[Learn more](#)



PRIMUS
S-01

[Learn more](#)

| | | | | | | |
|---|-----------------------------|-----------------------------|-----------------------------|-----------------------------|------------------|-----------|
| Made in France | X | X | X | X | X | X |
| Guaranteed in France <i>(for other countries, please contact us)</i> | 3 years | 3 years | 3 years | 3 years | 3 years | 3 years |
| Model | Rear-view mirror | Dashboard | Rear-view mirror | Dashboard | Rear-view mirror | Dashboard |
| Removable (installation option) <i>exclusive to ATA</i> | | X | | | | |
| 1001TAXIS - Trip booking application (Learn more on WWW.1001TAXIS.COM) | | | | | | |
| Receive bookings directly to the taximeter (with the BOX Connect) <i>exclusive to ATA</i> | X | X | | | | |
| User-friendly navigation | | | | | | |
| Four push buttons | Backlit and touch sensitive | Backlit and touch sensitive | Backlit and touch sensitive | Backlit and touch sensitive | Standard | Standard |
| Control dial <i>exclusive to ATA</i> | X | X | | | | |
| Contextual menu bar <i>exclusive to ATA</i> | X | X | | | | |
| Main features | | | | | | |
| Trip progress bar <i>exclusive to ATA</i> | X | X | X | X | | |
| Dimming of rear vehicle lights | X | | X | | | |
| Digital rate label <i>exclusive to ATA</i> | X | X | | | | |
| Automatic rate change | X | X | X | X | X | X |
| Automatic selection of day/night rate | X | X | X | X | X | X |
| Automatic summer/winter time adjustment | X | X | X | X | X | X |

**AIR W**[Learn more](#)**POWER HD**[Learn more](#)**AIR S**[Learn more](#)**POWER UP**[Learn more](#)**PRIMUS
RS-01**[Learn more](#)**PRIMUS
S-01**[Learn more](#)

| | | | | | | |
|--|------------------|------------------|-----------------------|-----------------------|--------------------|--------------------|
| Automatic brightness control | X | X | X | X | X | X |
| Automatic display of the minimum of fare | X | X | X | X | X | X |
| Manual management and selection of extras | X | X | X | X | X | X |
| Automatic power off in the event of prolonged inactivity | X | X | X | X | X | X |
| Display of odometer and trip meters | X | X | X | X | X | X |
| Speed information | | | | | | |
| Vehicle speed information | X | X | X | X | X | X |
| Gimbal sensor | X | X | X | X | X | X |
| Compatible CAN BUS | X | X | X | X | X | X |
| Technical features | | | | | | |
| Display unit | TFT screen | TFT screen | Pure-black LCD screen | Pure-black LCD screen | LED segment screen | LED segment screen |
| Dimensions (width x height x depth) | 278 x 82 x 23 mm | 150 x 50 x 12 mm | 278 x 82 x 23 mm | 157 x 57 x 17 mm | 278 x 82 x 28 mm | 165 x 53 x 22 mm |
| Weight | 280 g | 90 g | 280 g | 130 g | 280 g | 205 g |
| Removable SD Card | X | X | X | X | | |
| Environmental features | | | | | | |
| Operating temperature from -25°C to +70°C | X | X | X | X | X | X |
| Storage temperature from -40°C to + 85°C | X | X | X | X | X | X |
| Humidity conditions : Maximum of 93% relative humidity | X | X | X | X | X | X |
| Electromagnetic operating class: E3 | X | X | X | X | X | X |
| Mechanical operating class: M3 | X | X | X | X | X | X |